

Sustainability in commercial laundering processes

Module 1 Usage of water

Chapter 7

Glossary: Important parameters



AOX

Adsorbable organic halogen (X) compounds in waste water in mg/l (halogens are chloride, iodine and bromine. Chlorine is the most important element of these regarding waste water)

BOD

Biological **O**xygen **D**emand, indication of pollution load in water susceptible to biological degradation, expressed in oxygen consumption per litre water

BOD₅

Biological **O**xygen demand of waste water, indication of pollution load in water susceptible to biological degradation, expressed in the oxygen consumption per litre water in 5 days under standard conditions



COD

<u>Chemical Oxygen Demand, indication of pollution load in water</u> susceptible to chemical oxidation, expressed in the oxygen consumption per litre water necessary to achieve this degradation*

- COD is equal to or larger than the BOD. The difference between COD and BOD is an indication of the part of the pollution load which is not biodegradable.
- The quotient of COD and BOD is a measure for biodegradability. This
 quotient often appears in limiting values



Conductivity Electrical conductivity, indication of the salt

concentration in the water, in mS (Siemens)/cm

(usage of a special measuring device)

Einwohnerwert, German unit for the pollution level and the

volume of the waste water



Heavy metals

Heavy metals are e.g. cadmium, arsenic,copper and zinc. In soil and water, they are harmful pollutants. They are present in human and animal waste water. In laundering process, especially heavily soiled workwear contains heavy metals. Once in the environment, it is nearly impossible to get rid of them because they do not decompose.

Kjeldahl Nitrogen

Nitrogen concentration in the water determined by the Kjeldahl analysis method, in mg/l



MW	Molecular weight in g/mol
----	---------------------------

turbidity of the waste water is expressed

pH 7 = neutral

pH < 7 = acid

pH > 7 = alkaline



SDI

Silt Density Index, membrane fouling potential of the suspended solids

Settleable solids/ Suspended solids/ Settling agents Particulate inorganic and organic material contained in water. Together water and settleable solids are a suspension. In sewage treatment plant, they get separated from the water by gravity. This procedure is located in a sedimentation tank and/or sand traps.

Method of identification: "Imhoff-funnel, 30 minutes time. Settleable solids can also load waste water because agents may partly dissolve



TSS Total suspended Solids in the waste water, suspended

means non-dissolved particles

Water hardness Hardness of water is caused by dissolved inorganic

salts, particularly carbonates, sulphates and chlorides of

calcium and magnesium.

Hardness is usually expressed in mmol/l

Water hardness table see chapter 2

WW Waste water

WWTP Waste water treatment plant